

Declaration of Performance (DoP) In compliance with EU regulation 305/2011, Annex III		6106-T6	
For the construction product		Extruded aluminium sections	
1. Unique identification code of the product type:		EN AW-6106 T6/ EN 755-9	
2. Type, batch or serial number or any other element allowing identification of the construction product in compliance with Article 11(4):		Extruded section according to 15008:2005 / EN AW-6106 T6 according to EN 755-1	
3. Use(s) of the construction product intended by the manufacturer in compliance with the applicable harmonized technical specification:		Indoor and outdoor areas of load-bearing structures	
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in compliance with Article 11(5):		Hydro Extrusion Puget SAS ZA du Camp Dessert Nord – France 83488 Puget sur Argens Tel : +33 (0) 498112000 ; Fax : +33 (0) 494452344	
5. Name and contact address of the authorized representative commissioned with the tasks under Article 12 (2), if any:		Not appointed	
6. System(s) for assessment and verification of constancy of performance of the construction product in compliance with Annex V:		System 2+	
7. If the declaration of performance concerns a construction product that is covered by a harmonized standard:		The notified body (DNV) performed the initial inspection of the manufacturing plant and of factory production control, as well as continuous surveillance, assessment and evaluation of factory production control in compliance with System 2+ and issue certificate 2388-CPR-07402 confirming conformity of the factory production control with the requirements set out in Annex ZA of EN 15088:2005 and 2388 – CPR – 22 – 095 – 17 conforming EN 1090-1	
8. If the declaration of performance concerns a construction product for which a European Technical Assessment was issued:		Not applicable	
9. Performance declared:			
Essential characteristics	Performance	Harmonized technical specification EN 755-9	
Dimensional and shape tolerances	In compliance with standard		
Mechanical characteristics	In compliance with standard		
Flat profiles			
Wall thickness t (mm)			
≤ 10	min. max. NPDPD	Yield strength R _{p0.2} [MPa] min. max. NPDPD	Elongation A [%] min. max. NPDPD
	250 200	200 8	6 75
Hollow profiles			
Wall thickness t (mm)			
≤ 10	min. max. NPDPD	Yield strength R _{p0.2} [MPa] min. max. NPDPD	Elongation A [%] min. max. NPDPD
	250 200	200 8	6 75
Weldability	Class I	EN 1999-1	
Bendability	B3	EN 1999-1-3	
Fatigue strength	NPD	EN 1999-1	
Wear resistance	Table 3.1a		
Chemical composition			
Elements min max	Si Fe Mn Cu V	Mg 0.05 0.20	Cr Ni Zn - - -
Elements	Ti Ga	Other (each) 0.80	Other (total) 0.10
min max	- -	- 0.05	Al Rest 0.10
			Remark 0.10
10. The performance of the product according to numbers 1 and 2 is in accordance with the performance declared according to number 9. Only the manufacturer under 4 is responsible for preparing this declaration of performance.			

Signed for and on behalf of the manufacturer by:

Name and function:

Benoît DURET (Quality manager)

Place, date, signature:

Puget Sur Argens, 17/06/2025

